

RAM 4X4 SPECIFICATION

General	3/4 ton, long box, 4x4, ...
Year	2016
Make/Model	Ram 2500
Power plant	V8 Gas 5.7L minimum
Transmission	Automatic
Gear ratio	4x4, 3.73/ limited slip.
Tires	All terrain
Wheels	Steel
GVWR	
Cab Interior	40/20/40 split seat Standard Audio package Cruise Control Body upfitter switches (min 4) Electric Brake controller Air conditioning Tilt steering
Body exterior	Rear step bumper Color - School bus yellow or MFG equal
Misc	Extra key/FOB Full size Spare wheel/tire All Manufactures standard offerings Trailer tow package including reciever hitch
DOT Option package.	See Attached
Options	% off MFG. list

Paint	Dupont Chrome Yellow 6578X, School Bus Yellow or manufactures' equal.
Cab Protector Screen	WeatherGuard No. 1 906-X or equal painted to match the truck cab.
LED Warning Beacons	Dual flashing LED beacons affixed to cab shield/protector
LED Beacon specifications	LED Amber Flashing Beacons - Federal Signal Model Federal Signal flashing light part #252650-02NYS DOT or Star Warning Systems flashing part #255HTCL-A-NY or Whelen flashing part #L21-NYS. controlled by a fused/breakered, pilot lighted and labeled switch mounted in the dash.
Striping	Tail gate striping ; provide forty-five (45) stripes as 3M™ reflective tape, Dark Blue 580-75 or 680-75 Scotchlite™ reflective series by 3M™ (or equal providing a dark blue reflectivity). It shall be provided in width; Six (6) inch wide, Eighteen (18) inch on center. (intervals center to center when measured perpendicular to the stripe). This striping shall slope downward to street-side (driver's side of vehicle) of the vehicle at a forty-five degree (45°) angle from horizontal. This spacing location (relative to overall surface being striped) shall provide the maximum number of full width blue stripes across the rear of vehicle. (Diagram provided upon request)
Fire Extinguisher	2.5 pound dry chemical ABC rated with mounting bracket.
Safety reflector kit	Three-piece Triangle "Flare" kit with storage box