

METRO-NORTH RAILROAD

SPECIFICATION 3FX

Rev 11/2015

General Description: **2 MAN H.D. SERVICE VAN**



<u>Item</u>	<u>Minimum Specification Component, Size and Capacities</u>	<u>Vendor Please State: Specific Component, Size and Capacities To Be Supplied</u>
1.00 Make/Model	Specify: Vehicle Make : _____ , Model: _____	_____.
1.00a Event Data Recorder	Is this vehicle equipped with an Event Data Recorder installed by the chassis manufacturer.	<u>YES / NO</u>
1.01 GVW	8,500 lbs. (min.)	_____ <u>G.V.W.</u>
1.02 Payload	Basic Chassis 3,200 lbs. (min.)	_____ <u>lbs.</u>
1.02 Wheelbase	135" (min.)	_____ <u>"W.B.</u>
1.04 Height (max.)	Please state. (All vehicles with an unloaded height of over 11 ft. placards showing the maximum vehicle height are to be placed on the body near the highest point, and on the instrument panel, both within the drivers line of sight.	_____.
1.10 Frame	H.D. truck frame. RBM to be consistent with G.V.W. and wheelbase requirements.	_____.
1.11 Front Axle	Non-Driving, 3,900 lbs. (min.)	_____.

Spec 3FX	Minimum Specification Component, Size and Capacities	Vendor Please State: Specific Component, Size and Capacities To Be Supplied
<u>Item</u>		
1.12 Rear Axle	Driving, 5,700 lbs. (min.)	_____.
1.13a FT. suspension	3,600 lbs. total (min.) w/H.D. stabilizer bar.	_____.
1.13b R. suspension	5,700 lbs. total (min.)	_____.
1.14 Steering	Full Power	_____.
1.15 Transmission	H.D. 4 Speed Automatic w/OD	_____.
1.16a FT. tow hooks	N.A.	_____.
1.20a Tires & wheels	LT 215/85R16E mounted on H.D. rims. M+S tread front and rear.	_____.
1.20b Spare/mounting	M+S Tread mounted on rim with tools provided, and mounted in a carrier. If mounted outside vehicle, must be a locking carrier.	_____.
1.20c Tire clearance	Sufficient clearance to be maintained up to rated G.V.W.	_____.
1.30 Brakes, type	H.D. Disc front/rear, power assisted w/four wheel ABS.	_____.
1.40 Engine	Gasoline engine 8 cyl. 5.4 Lt. (min.)	_____.
1.41 Cooling system	H.D. system protected to -30°F.	_____.
1.42 Fuel system	30 gallon cap.(min.) Locking fuel caps.	_____.
1.42a Fuel Types	Vehicle must be capable of operating on reformulated gasoline or diesel fuel as defined in the Federal Clean Air Act (CAAA), and N.Y.S. Clean Fuel Fleet Program.	_____.
1.43 Elect. system	Alt. 60 amp.(min.), Battery 450 CCA@0°F.	_____.
1.45 Exhaust system	To be shielded to prevent overheating and contact with body and be routed to prevent fumes from being discharged at operators station.	_____.
1.50 Body type	Enclosed van with right side panel doors W/O windows & rear panel doors W/windows.	_____.
1.51a Interior seating	2 individual front seats upholstered in H.D. vinyl, w/high back (or individual headrests), Seat belts for each passenger. Driver and right passenger dual air bags.	_____.
1.51b Interior	Headliner over drivers compartment, arm rests on each door, full length rubber floor covering, dual front sun visors.	_____.
1.51c Instruments	Include: Speedometer/odometer, ammeter or voltmeter fuel & temp. gauges, oil pressure light.	_____.
1.52a Interior Lights	Door and dash operated.	_____.
1.52b Horn	Electric	_____.

Spec 3FX	Minimum Specification Component, Size and Capacities	Vendor Please State: Specific Component, Size and Capacities To Be Supplied
<u>Item</u>		
1.52c Wiper/Washer	Two Speed Electric w/ intermittent.	_____.
1.52d Heater/AC	Heater/Air Conditioner w/manual temp. control, factory installed.	_____.
1.52e Radio	Std. AM/FM	_____.
1.53a Reflector kit	Dot Approved Triangle	_____.
1.53b Fire extinguisher	10BC (min.) Cab mounted, secured with a quick release strap type clip.	_____.
1.53c Shipping paper pouch	10"x15" w/clear vinyl front, mounted on inside of drivers door. J.J.Keller DR-8-R (or equal).	_____.
1.54a Hood lock	Inside Cab.	_____.
1.54b Mirrors	Dual, OEM, below eye level, manual foldaway mirrors w/convex section. Min. approx. size: 9" x 6.5".	_____.
1.54c Grab handles	N.A.	_____.
1.54d Backup alarm	Audible type, frame mounted.	_____.
1.54e Backup Camera	OEM backup camera w/ built in dash mounted monitor or aftermarket rear vision camera system w/ 5" monitor, LED backlit display, 180 degree view, automatic trigger when transmission place in reverse mounted to dash area in drivers full view w/o obstructing view out windshield (Zone Defense ZD.322.R or approved equal)	_____.
1.56a Rust proofing/undercoating (cab & body)	Std. Vehicle and Truck Body Manufacturers process permitted if 5 year Rust Perforation Warranty is included with vehicle and truck body. Otherwise a non-hardening rust proofing process such as Tufflex, or Ziebart must be applied to: all fender, hood, trunk, door cowl, rocker, body and engine compartment panel inside surfaces.	_____.
1.57a Exterior paint	Mfgs. standard polyurethane enamel Choice of any standard manufacturers color	_____.
3.00 Body		
3.01a Right side door	Panel type doors with fixed windows. Adrian Metal Products Model 60 (or equal) wire screen to be installed on interior of door glass.	_____.
3.01b Rear doors	Panel type doors with fixed windows. Adrian Metal Products Model 60 (or equal) wire screen to be installed on interior of door glass.	_____.

Item



3.02 Cargo, cab partition

Adrian Metal Products (or equal), Drivers side solid panel #S1, Center panel #M3H perforated, hinged door w/plexiglass cover panel #PA 5-2 , Curbside panel #C2 perforated panel w/plexiglass cover #PA 5-1. Head impact pads, Model #PA-4 mounted behind each seat.

_____.

3.03 Floor mat

Full size 1/4" thick rubber mat to cover entire cargo area. Adrian Metal Products Series 88 (or equal).

_____.

3.04 Spare tire retainer

Relocated to cargo partition behind passenger seat. Adrian Metal Products (or equal) #PA-1, PA-3.

_____.



4.00 Misc. body Items

4.03 Wiring

All wiring to be routed in plastic wire looms. To be secured by tiedowns and fasteners. Rubber grommets to be used wherever wiring passes through a body panel. Wires must not be allowed to droop be subject to being pulled or pinched.

_____.

4.04 Lighting

To Conform to FMVS 108.

_____.

Spec 3FX	Minimum Specification Component, Size and Capacities	Vendor Please State: Specific Component, Size and Capacities To Be Supplied
<u>Item</u>	<u>Capacities</u>	<u>To Be Supplied</u>
4.04a Rear lighting	Mfgs. Standard body lighting	_____.
5.00 Misc.		
5.01a Manuals	Supply the Following at Time of Delivery.	
5.01b Vehicle (Operators)	One Per Vehicle Plus One for Files.	_____.
5.01c Vehicle Service (Chassis)	Two Sets Per Order	
5.02a Warranty	To be completed and supplied at time of delivery. Warranty on Vehicle and Components will start at in service date by Metro-North.	_____.
5.04a Inspection	All vehicles are subject to Inspection by Metro-North Automotive during assembly.	_____.
5.07 Striping	<p>The vehicle cab and body shall be striped and decaled both sides. The striping package shall consist of one, 4 inch wide stripe, MTA Metro North Railroad logo on both front door and rear of vehicle, US DOT decal (vehicles w 10,000 lb or greater GVW), Vehicle numbers on both sides and rear. See Attached Spec</p> <p>Due to the various cab and body configurations, all striping will not commence without the prior approval of the Assistant Director of Automotive or his designee, for the proper configuration.</p>	_____.
6.00a Weight Analysis	<p>Vehicle cargo capacity may not be less than the minimum shown. M-N reserves the right to weigh a sample vehicle(s) to verify the capacity.</p>	
	a. Basic Chassis	_____ lbs.
	b. Miscellaneous Components	_____ lbs.
	c. Total	_____ lbs.
	d. Remaining Capacity	_____ lbs.
	e. Minimum Cargo Capacity Required	_____ 3,200lbs.
6.01 Emission/Safety Requirements	Vehicle(s) are to be in compliance with Federal and New York State Safety & Emission requirements for current model year vehicles, to permit registration of vehicle in New York State.	
6.02 Layout drawing	If requested, the vendor is to supply a layout drawing (to scale) to clarify any engineering point, or component placement.	_____.
6.03 Price breakdown (per unit).	Chassis	_____.
	Body	_____.
	Training & Misc.	_____.
	Total Price	_____.

Spec 3FX	Minimum Specification Component, Size and Capacities	Vendor Please State: Specific Component, Size and Capacities To Be Supplied
<u>Item</u>		
6.04 Assembly	Point of Completed Vehicle Assembly	_____.
OPTIONS		
OP-1 Strobe light	Warn Model 851 Super Hi-Intensity, or Federal model 34012 (or equal) Color: amber, Mounted on center of cab enclosed in an expanded wire mesh cover. Controlled by a dash mounted switch w/pilot light and labeled.	
	Total Option Price	_____.
OP-2 Ladder racks	Adjustable overhead ladder and material rack w/slide down ladder retainer on curb side. Crown Metal Products L4063 w/Slide down upgrade L124. (or equal).	_____.
	Total Option Price	_____.
OP-3 Body Package #1 OP-3a Drawer Cabinet	Module to be placed behind partition, drivers side. Size: 36"W x 46"H x 12"D. To include shelf module on left side min. 4 shelves, Storage module on right side to include: 1 storage cabinet, 4 small drawers, and 2 large drawers. Adrian Module #MD503 (or equal).	_____.
OP-3b Utility Shelf Rack	Module to be placed behind OP-4a, over drivers side rear wheel well. Size: 42"W x 46"H x 16"D. To include 4 shelves w/dividers, and bolt in drawer module. Adrian Module #46. (or equal). To include locking door kit on bottom section. Adrian #DK544 (or equal).	_____.
	Total Option Price	_____.



Spec 3FX

**Minimum Specification
Component, Size and
Capacities**

**Vendor Please State:
Specific Component,
Size and Capacities
To Be Supplied**

Item

[Spec3FX]