

Detailed Specifications

Two (2) 2016 Ford Transit 150 (medium roof) XL Cargo Van. WB: 130", Length: 220", GVWR: 8600 lbs.
Engine: 3.5L EcoBoost® V6 Engine
Alternator: Heavy Duty
Batteries: Dual Heavy Duty 78 amp/hr
Axle ratio: 3.31 Limited Slip
Transmission: 6 – Speed Automatic Overdrive with Selectshift
Tires: LT 235/65R16.0 Black Side Wall AS
Brakes: 4-Wheel Disk with ABS
Radio: AM/FM Stereo
Seats: Pewter Gray Vinyl, 2-way Manual (fore/aft/recline) Driver & Front Passenger, Driver-Side Arm-Rest Bucket Seats
Mirrors: Long Arm – Power Heated with Turn Signals
Additional Equipment Groups or Options: Air conditioning – Manufactures Standard Factory-Installed Upfitter Switches Back Up Alarm Window Group: Fixed Rear-Door Glass with Fixed Passenger-Side Door Glass Keyless Entry-Keypad Auxiliary Fuse Box with Modified Vehicle Wiring System Rear-Window Defogger Reverse Sensing System Right Side Sliding Door Cruise Control with Message Center 110-Volt AC Outlet Floor Covering-Vinyl, Front & Rear Power Door Locks & Windows (Standard) Remote Keyless Entry (Standard) Front License Plate Bracket 12 volt hot point Rear Doors – Hinged, 180 Degree Opening Rear View Camera (Standard) Four (4) Complete Key Sets
Color: Exterior – Oxford White Interior – Vinyl, Pewter Gray
Rear Bumper: Black, Molded-in-color with Integral Step

Detailed Specifications

DESCRIPTION: Furnish and Install Aluminum Van Shelving and Accessories
Shelving Manufacture: Ranger Design
Shelving Unit Specifications: F316 Ranger Design Service Package, Proline Aluminum Contractor Package and Sliding Door Partition with Tempered Glass Window, Ranger part# 3068-FTM
Accessories Supplied and Installed: Strobe Lights: Fourteen (14) Federal Signal - MicroPulse Ultra, Amber/Amber, part# MPS600U-AA. Mounted as follows: Two (2) mounted in front grill and wired to independent switch with label (position to be determined at time of installation) Four (4) mounted on rear of body and wired to independent switch with label (position to be determined at time of installation) Four (4) mounted on each side of body and wired to independent switch with label (position to be determined at time of installation) Switch Control: Mount one (1) Federal Signal – SW200-12. (position to be determined at time of installation)